Taro™ Pumps

Authorised Dealer

- FITTED WITH COPPER ROTOR
- ANTI CORROSIVE LIQUID
- SINGLE LENGTHY GUNMETAL BUSH

PUMP SETS	DETAILS
OUTPUT POWER	15 hp/ 11 kw
NO OF POLES	2 Poles
SPEED	2880 rpm
RATED VOLTAGE	415 V, 50 Hz, Three Phase
OPERATING VOLTAGE RANGE	350 - 440 V, 50 Hz, Three Phase
RATED CURRENT AT	415 V 29 A
RATED HEAD	240 meters
HEAD RANGE	180 - 264 meter
MOTOR TYPE	Wet
NET WEIGHT	75.5 Kg
GROSS WEIGHT	80 Kg
NET WEIGHT	64 Kg
GROSS WEIGHT	70.5 Kg
GROSS WEIGHT	150.5 Kg
CONNECTION TYPE	Star/Delta
DUTY	S1
THRUST RATING	28.7 Kg / SqCm
CABLE	2 x PVC Insulated Cable - 3 Core Flat 4 Sq.mm, Black Color 3 Meter Length
IMPELLER TYPE	Radial
OPERATING TEMPERATURE RANGE	10 °C - 60 °C
STARTING TORQUE	125
CLASS OF INSULATION	'B' Class
CERTIFICATION	Non-ISI
STARTING CAPACITOR	125
STAGE	30
PHASE	3
DELIVERY PIPE SIZE	50

Kaveri-SN
AE-12

ಸಹಾಯಕ ಕಾರ್ಯಪಾಲಕ ಅಭಿಯಂತರರು
ಶೆಟ್ಟಿಹಳ್ಳಿ ಉಪವಿಭಾಗ, ದಾಸರಹಳ್ಳಿ ವಲಯ
ಬೃಹತ್ ಬೆಂಗಳೂರು ಮಹಾನಗರ ಪಾಲಿಕೆ
ಎಸ್.ಎಂ. ರಸ್ತೆ, ರವೀಂದ್ರನಗರ, ಬೆಂಗಳೂರು.

SNS PUMPS ★ 073 ★ Bangalore-560

SNS Pumps
No. 324, 8th Maile, 2nd Cross,
Ramaiah Enclave, T. Dasarahalli,
Bangalore Urban - 560 073

GST 29AMQPV2319H1ZH
Phone: 95354 22448
snspumps@gmail.com

Texmo Industries
Est. 1956

Scanned by CamScanner